

705, 710 & 726 Personal Attack Transmitters



Images are not shown at actual size.

- Reliable, secure Scantronic 868 MHz narrow-band radio operation
- Dual button operation
- 2-channel version for alert (pre-warning) + alarm signals
- Extended and standard range options
- Lithium battery-powered (supplied)

Why settle for less when your staff need help most?

Hopefully, your staff will never need to find out why our personal attack transmitters are so highly regarded. But should they ever be attacked, they'll quickly realise why over 750,000 people worldwide trust them with their lives.

The 705, 710 and 726 models all come with 10mW transmitting power compared to the usual 0.25mW. And, to ensure your transmitter is always working, the long-life lithium battery sends a signal when less than one month's operation remains.

All models are designed to prevent accidental activation and a variety of wearing options – hand-held, neck pendant or clip-on – means there's a style to suit everyone.

With many other state-of-the-art features (see overleaf), no other range of personal attack transmitters is better equipped to draw attention to a member of staff when they are under attack.



705, 710 & 726 Personal Attack Transmitters

TECHNICAL SPECIFICATION

Part number	710rEUR-00	705rEUR-00	726rEUR-50	726rEUR-60
Description	Dual operation personal attack transmitter	2-channel personal attack transmitter	Extended range, dual operation personal attack transmitter	Standard, dual operation personal attack transmitter
Channels	1	2 (alert + alarm)	1	1
Operating frequency	868.6625MHz @ 20KHz bandwidth. CE tested to I-ETS 300 220	868.6625MHz @ 20KHz bandwidth. CE tested to I-ETS 300 220	868.6625MHz @ 20KHz bandwidth. CE tested to I-ETS 300 220	868.6625MHz @ 20KHz bandwidth. CE tested to I-ETS 300 220
Transmission power	10mW	10mW	10mW	10mW
Free space radio range	> 1000m	>600m	>1000m	>600m
Power supply (battery)	3v CR2 Li	3.6v Li 1/2 AA Not user replaceable	3.6v Li 1/2 AA Not user replaceable	3.6v Li 1/2 AA Not user replaceable
Typical battery Life	3-5 years	3-5years	3-5 years	3-5 years
Temperature range	-10 to +55 °C	-10 to +55 °C	-10 to +55 °C	
Dimensions	58 x 40 x 16	104 x 46 x 30	163 x 46 x 30	104 x 46 x 30
Weight	34gm	60gm	65gm	65kgm
Colour	White	Dark Grey	Dark Grey	Dark Grey
Compliance	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II PD6662:2004	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II PD6662:2004	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II PD6662:2004	EN50131-2 Grade 2, EN61000-6-3:2001, environmental class II PD6662:2004

COMPATIBLE RECEIVERS

Scantronic 9960rEUR-08 & 16 RFX receiver interfaces (not 705rEUR-00)

Scantronic Homelink 55 24 zone radio alarm panel (not 705rEUR-00)

Scantronic Homelink 75 32 zone radio alarm system (not 705rEUR-00)

Scantronic 762rEUR-00 2-channel receiver

Scantronic 768rEUR-00 8-32 channel receiver

Menvier MRNODE receiver interface (not 705rEUR-00)

APPLICATIONS

- Portable personal attack transmitters
- Protection of patrolling guards
- Protection of garage forecourt attendants
- Protection of medical and hospital staff
- Protection of retail store staff
- Protection of cash-in-transit crews



COOPER Security

www.coopersecurity.co.uk

Please contact your local dealer

