



**Feature**

- H.264 dual-stream video compression
- Compatible with Analog 960H/D1
- All channel 720P@25/30FPS realtime recording, 1/4CH playback simultaneously
- 2\*USB2.0, USB Disk up to 32G(Kingston)
- Audio talk back supported
- Support 10M/100Mbit/s network interface
- Mobile surveillance supported,Including iPhone, iPad, Android
- Support browser IE 6.0 Above
- Free ISS Management software
- Free DDNS server: HDCCTVDDNS
- 1080P HD Diaplay
- 1 SATA, Max 3TB per HDD

<b>Model NO.</b>	<b>QH-D6008E</b>
OPERATION SYSTEM	LINUX
<b>VIDEO</b>	
VIDEO SYSTEM	NTSC/PAL Switch Selectable
INPUT	BNC*8,1.0Vp-p,75ohm
CVBS OUTPUT	NA
SPOT	NA
HDMI OUTPUT	1 HDMI Output
VGA OUTPUT	1 VGA Output
LOOP OUT	NA
<b>AUDIO</b>	
INPUT	4CH, RCA
OUTPUT	1CH, RCA
TALK BACK	YES
<b>CONTROL</b>	
MOUSE	2*USB2.0
IR CONTROLLER	YES
KEYBOARD	NA
<b>STORAGE</b>	
BUILD IN INTERFACE	SATA 2.6 *(1*(HDD 3TB )
<b>DISPLAY</b>	
DIVISION	1, 4, 9

ZOOM	Preview&Playback Zoom Support
<b>RECORDING</b>	
COMPRESSION	H.264(High profile)
RECORDING MODE	Manual/Schedule/Motion Detection/Sensor ( Optional )
RESOLUTION	Mode 1: 8CH 720P
	Mode 2: 4CH 720P + 4CH 960H
	Mode 3: 8CH 960H
RECORD FRAME RATE	8CH 720P@20fps,
QUALITY	Worst, Worse, Bad, Normal, Better, Best
<b>PLAYBACK</b>	
SYNC PLAYBACK	1, 4
SPEED	Normal, FF(1X, 2X, 4X, 8X,), Slow (1/2X, 1/4X, 1/8X)
SEARCH METHOD	Time, Event, Channels and Calendar
<b>COMMUNICATION</b>	
REMOTE ACCESS	IE ( 10.0 and below), ISS ( Windows XP/WIN7/WIN8 ), ISS MOBILE2 ( IOS, Android )
REMOTE OPERATION	Remote view, remote playback, remote setup
NETWORK SERVICE	TCP/IP、PPPOE 、 DDNS、 FTP、 NTP UPNP
MOBILE DEVICE	Iphone, Ipad, Android
3G EXTERNAL MODULE	Yes, with USB 2.0 Port
WAN RJ45	10/100Mbit/s
WIFI EXTERNAL MODULE	Yes, with USB 2.0 Port, 100Meters
GUI INTERFACE	Supported GUI 16 Bit True Color
PTZ PROTOCOL	PELCO-D, PELCO-P, etc 17 kinds of protocol
<b>BACKUP</b>	
INTERNAL	NA
EXTERNAL	2*USB2.0
NETWORK	YES
FILE FORMAT	AVI/dav
<b>GENERAL</b>	
ALARM IN/OUT	NA
RS-485	1
RS-232	NA
UNIT DIMENSION(mm)	260(L) x 44(H) x 221(W)
OPERATION TEMPERATURE	10° ~ 40°
WORKING HUMIDITY	10% ~ 90%
POWER CONSUMPTION	DC 12V,2A, <6W (Exclude HDD)