DT16 - IF16/L - IF16/T

DT16 EN 50131-2-4 / GRADE 2 DUAL TECHNOLOGY



F16/L EN 50131-2-2 / GRADE 2 PASSIVE INFRARED






F16/T EN 50131-2-2 / GRADE 2 PASSIVE INFRARED





ALARM DIRECTION

Buzzer with different sounds depending on the direction of the movement (IF16/L) $\,$





DT16

EN 50131-2-4 / GRADE 2 Dual Technology

DT16 is a dual technology detector, infrared and microwave at 10 Ghz suitable for creating a type of protection "curtain" for doors and windows. It has the back tamper, the antiopening tamper device, a signalling LED with its disabling jumper. It has alarm direction recognition.

Available colours: white, dark brown

IF16/L - IF16/T

EN 50131-2-2 / GRADE 2 Passive infrared, with high power LED

IF16 is an infrared detector, able to create a protective "curtain" barrier for doors and windows. It has an adjustable range between 3 mt and 5 mt and has some special features which make it very interesting as:

- led high light output for lighting function and/or alarm (only in the "L")
- alarm direction recognition (only in the "L")
- buzzer with different sounds depending on the direction of the movement (only in the "L")
- delay system activation

Available colours: white, dark brown (IF16/T) - white (IF16/L)

Technical Features				
	DT 16	IF 16/L	IF 16/T	
EN 50131-2-4 / GRADE 2	YES	-	-	
EN 50131-2-2 / GRADE 2	-	YES	YES	
RANGE	from 3 to 5 mt	from 3 to 5 mt	from 3 to 5 mt	
ANGLE	165°	165°	165°	
CURTAIN LENS ORIENTATION	YES	YES	YES	
ALARM TIME	4"	4"	4"	
PROGRAMMABLE ALARM DELAY	-	YES	YES	
HIGH POWER LED FOR LIGHTING AND/OR ALARM	-	YES	-	
WALK TEST'S LED	YES	YES	YES	
DOUBLE SOUND BUZZER (ENTRANCE/EXIT)	-	YES	-	
ANTIOPENING TAMPER	YES	YES	YES	
RFI PROTECTION	30 V/m	30 V/m	30 V/m	
TEMPERATURE COMPENSATION	YES	YES	YES	
POWER SUPPLY	10 - 15 Vdc	10 - 15 Vdc	10 - 15 Vdc	
CONSUMPTION IN STAND BY	18 mA	12 mA	12 mA	
HOUSING	ABS	ABS	ABS	
OPERATING TEMPERATURE	from -25°C to +55°C			
DIMENSIONS		37 x 130 x 37 mm		