
## **Push Button Series**



|  |   | UYAL  |
|--|---|---|
| 1-PBI-L  |   | R-888-PBI-S   |
| nfrared Sensor Push Button   | Flush Mounted IR Push Button  |   |
| Made by Order  | (Active o   | listance: 4-stage adjustment within 2~10cm)   |
| reen&Red) (LED OFF) (LED ON:Green&Red)   | Standby   |   |
| ger door lock without touching, suited in fields with high   | central guidin  | g LED status adjustable red/green LED frame<br>design is thin and aesthetics, Bi-color LED ring shine and   |
| arrious sites: Slim type, US type and EU type.<br>ity to install it on the decoration surface on site rather<br>panels only.<br>ows door open under no power supply situation just by<br>suitable for installation as both door exit button and also<br>djusted from 1 cm to 6cm (With Additional Physical Button).  | light your life.<br>Infrared sensor<br>fields with high<br>US type and EL<br>LED ring color i<br>Anti-sunlight an<br>Waterproof ratir | design can trigger door lock without touching, suited in<br>hygienic standards.<br>I type for choice and installation on various sites.<br>s changeable according to user needs.<br>d infrared interference design<br>ng IP65, suitable for indoor and outdoor installation.<br>uding range is adjustable according to the needs. |
| 1  | Voltage   | DC 12-24V   |
| tandby: 30mA / Max. during activation: 75mA  | Current   | DC 12V Standby: 35mA / Max. during activation: 65mA   |
| / 125VAC 0.3A  | Contact capacity  | 30VDC 1A / 125VAC 0.3A  |
| (1A / VAC/VDC 30V)<br>2 mm     6 mm  | Output Contact  | Relay(Form C)   |
| $\begin{array}{c} 10 \\ \hline \\ $  |   |   |
|  |   |   |
| 2  mm $6  mm10  m$ $10  m32  m$ $10  m32 \text{ m} 10 \text$  | → 9 ←<br>→ 3 →<br>EXT<br>Sight  |   |
|  | AR-PBI-888(US)<br>118(H)X81(W)X9/42(D)<br>SOYAL+EXIT  |   |
| $2 \text{ mm} \qquad 6 \text{ mm} \qquad 10 \text{ cm} \qquad 10  $ |   |   |
|  | AR-PBI-888(EU)<br>86(H)X86(W)X9/42(D)<br>SOYAL+EXIT   |   |
|  | www.so  | yal.com V230106   |