



# PE CLEANER HEAVY DUTY

## CLEANER FOR PE, PP, PVDF AND PB



### STORAGE CONDITIONS

Shelf life: At least 36 months after production.  
 Stored in unopened packaging between +5°C and +25°C.  
 Close packaging properly after use and store in a dry, cool, and frost-free location.  
 Limited shelf life after opening.

### PRODUCT DESCRIPTION

Cleaner for PE, PP, PVDF and PB.

### FIELD OF APPLICATION

For cleaning and degreasing pipes, sockets and fittings of PE, PP, PVDF and PB. Also suitable for cleaning welding equipment.  
 Use in combination with Griffon Cleaner Cloth.

### PROPERTIES

- Very Powerful cleaning properties
- Rapid and complete vaporization
- With special dosing cap

### APPLICATION

**Coverage:** Indication of the number of joints per 1 L:

| Ø | 32  | 40  | 50  | 63  | 75  | 90  | 110 | 125 | 160 | 200 | 250 |
|---|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| # | 800 | 700 | 650 | 550 | 330 | 250 | 160 | 140 | 90  | 50  | 35  |

### Directions for use:

1. Apply cleaner to a Griffon Cleaner Cloth. 2. Clean and degrease surfaces. 3. Remove any condensation with Griffon Cleaner Cloth and allow surfaces to dry properly. Close packaging immediately after use.

### TECHNICAL SPECIFICATIONS

|                    |                        |
|--------------------|------------------------|
| Chemical base:     | Mixture of solvents    |
| Colour:            | Colourless             |
| Density approx.:   | 0.70 g/cm <sup>3</sup> |
| Viscosity:         | Liquid                 |
| Viscosity approx.: | 1 mPa·s                |

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.